

AEC T1 Series line interactive UPS system.(700VA-1kVA)



AEC T1 Series line interactive UPS system.(700VA-1kVA)

Product Benefits:

- T1 Series 500VA-1kVA
- Compact and stylish, ideal for office or home.
- Excellent performance and reliability, designed for maximum equipment protection
- Advanced MCU control technology, enhancing ups performance.
- Competitively priced
- High efficiency
- 500Va, 700Va, 1kVa, powerful enough for desktop PC's.
- Conforms to all necessary safety and CE specifications
- No noise, place it on your desktop
- Simple, easy to read LCD display
- Fast, low voltage protection buck and boost
- Predicting mains failure
- Automatic voltage regulation saving battery power.
- Low battery protection preventing deep discharge.
- Advanced battery management.
- Modem, phone line and peripheral equipment protection.
- Hot battery swap, no need to witch off UPS (except 1kVa model)

T1 Series

With its sleek case and hi-tech fascia PHD's T1 series is a reliable, cost-effective UPS. Looking equally at home in the office or domestic environment the T1 is ideal for applications requiring basic, no nonsense, economical power protection.

Power Ratings

Three power ratings are available, 500VA, 700VA and 1kVA with innovative mobile phone style LCD display. Each unit's display will keep you quickly updated on mains and battery status

AEC T1 Series line interactive UPS system.(700VA-1kVA)

ensuring continuous protection of your equipment and data.

Protection

With a wide-ranging input voltage (rated voltage +25% / -30%) the Automatic Voltage Regulation (AVR) function of the T1 series ensures regulated power to your equipment even under poor supply conditions. T1 also protects your modem and phone line via a filtered socket, eliminating one of the most common causes of hardware failure. Also included is a peripheral protection socket offering mains filtering to protect valuable non-essential equipment. Under mains failure the T1 provides computer grade power and will start a controlled shutdown of your software and connected hardware, completely protecting your data and working documents

AEC T1 Series line interactive UPS system.(700VA-1kVA)

SPECIFICATIONS			
Maximum Capacity	500VA/300W	700VA/420W	1000VA/600W
INPUT			
Voltage	220/230/240VAC (+25% / -30%)		
Input Frequency	44Hz ~ 56Hz		
OUTPUT			
Output Voltage	220/230/240VAC ± 10% (On Battery Mode)		
Output Voltage Regulation	± 10%		
Output Frequency	46 ~ 54Hz		
Output Frequency (Battery Mode)	50 ± 0.1Hz		
Overload Capability	Delayed protection when the output is > 150% overload		
BATTERY			
Battery Type	Sealed lead-acid maintenance-free 12VDC/7Ah per cell		
Number of Batteries	1 cell	1 cell	1 cell
Backup Time (at Full Load)	13 minutes	9 minutes	13 minutes
Recharge Time to 90%	< 10 hours		
TRANSFER TIME			
AC to DC	< typical 6 ms		
INDICATION			
LCD	AC Mode, Battery Mode, Output Status, Battery Capacity, Overload, UPS Fault		
AUDIBLE ALARM			
Battery Mode	Long beeping		
Low Battery	Continuous beeping		
Overload	Short beeping		
DIMENSIONS			
W x H x D (mm)	90 x 165 x 325	90 x 165 x 325	120 x 210 x 380
WEIGHT			
Net Weight w/ Battery (kgs)	6.3	6.6	15
ENVIRONMENTAL			
Operating Temperature	-5 ~ +40°C		
Relative Humidity	< 90% (Non-Condensing)		
Audible Noise	<45dBA @ 1 Meter	<50dBA @ 1 Meter	<55dBA @ 1 Meter